

2559-RTD

8-Channel RTD Input Module



100Ω, 120Ω, 130Ω, 200Ω, 500Ω, 1000Ω, 10Ω,
9.03Ω

2,3, 4 wire
250μA
1000Ω per lead wire (max)

30VDC or VAC continuous

10Ω Cu: -100°C to 260°C (-148°F to 500°F)
100Ω Pt: -200°C to 850°C (-328°F to 1562°F)
120Ω Pt: -80°C to 260°C (-112°F to 500°F)

°C, °F, ohms (selectable)
±0.1°C, ±0.2°F
0.1°

100Ω Pt 0.9°C (1.6°F) from 0-60°C
Ωx100 0.36Ω from 0-60°C

25 mSec (all channels, no filtering)

The 2559-RTD is a high-speed 8-channel RTD input module designed to be compatible with the SIMATIC® 505 I/O base. The Model 2559-RTD translates RTD input signals into scaled temperature values.

>130db @ 60Hz

>80db @ 60Hz

1500 VDC channel-to-PLC

- CTI 2500 Series™ or Simatic® 505 base format
- 1500V channel-PLC backplane isolation
- Fast 25ms update time for all channels
- Detects open in RTD or field wiring
- Compensates for lead resistance

3 wire 100Ω platinum
Digital filtering enabled
Degrees C

standard CTI 2500-40F 40-position removeable connector, 14-22 AWG

2.8W @ 5 VDC
Single-wide

0° to 60°C (32° to 140°F)
-40° to 85°C (-40° to 185°F)
5% to 95% (non-condensing)
UL, ULC, CE, FM

8 RTD input channels

(Class 1, Div.2)

1.5 lb. (0.68 Kg)

Platinum 0.003850 (European DIN)
Platinum 0.003916 (American)
Platinum 0.003902
Platinum 0.003920
Copper 0.004274
Nickel 0.006720
Nickel 0.006178 (European DIN)



Control Technology Inc.

5734 Middlebrook Pike, Knoxville, TN 37921-5962
Phone: +1.865.584.0440 Fax: +1.865.584.5720
www.controltechnology.com

